



Help Logout

Main Menu | Search Form | Result Set | Show S Numbers | Edit S Numbers |
First Hit | Previous Document | Next Document |
Full | Title | Citation | Front | Review | Classification | Date | Reference | Claims | KWC |

## **Document Number 201**

Entry 201 of 422

File: JPAB

Nov 24, 1992

PUB-NO: JP404335997A

DOCUMENT-IDENTIFIER: JP 04335997 A

TITLE: BOILER TUBE FOR CITY REFUSE INCINERATOR

PUBN-DATE: November 24, 1992

INVENTOR-INFORMATION:

NAME

MORIMOTO, JUNJI

HAMAMOTO, TAKANORI

OTSUKA, TAKAO

KOYAMA, MASAHIRO

YAMADA, KATSUHIRO

TOYAMA, KAZUHIRO

ASSIGNEE-INFORMATION:

NAME

COUNTRY

HITACHI ZOSEN CORP N/A

APPL-NO: JP03104560 APPL-DATE: May 10, 1991

INT-CL (IPC): F28F 19/06; C23C 4/08; F22B 37/04; F22B 37/10; F23G 5/46; F28F

21/08

## ABSTRACT:

PURPOSE: To obtain a boiler tube for a city refuse incinerator, having excellent wear resistance and <u>corrosion resistance</u> by forming an allay film made of 15-55wt.% of <u>Cr</u> and the balance of <u>Ni</u> on an outer surface of a heat transfer tube by an explosion <u>spraying</u> method.

CONSTITUTION: A heat exchanger 5 is formed by aligning many heat transfer tubes 9 longitudinally between a left side wall 7 and a right side wall 8 in a lengthwise direction, and soot blowers 6 are provided on a back wall 10. A metal film 12 made of 15-55wt.% of Cr and the balance wt.% of Ni is formed on an outer periphery of part of the tube 9 group oppositely to drain vapor from the blowers 6 by an explosion spraying method. As a result, an increase in oxidation of the explosion spraying method is reduced as compared with that of a flame spraying method with lapse of time. Accordingly, the explosion spraying method can form a dense film having a high adhesive strength to provide an excellent high temperature resistance.

COPYRIGHT: (C) 1992, JPO&Japio

Main Menu | Search Form | Result Set | | ShowS Numbers | Edit S Numbers |



DB Name	<u>Query</u>	Hit C unt	Set Name
ALL	115 same 111	422	<u>L17</u>
ALL	115 and 111	1285	<u>L16</u>
ALL	corrosion resist\$4 same (chromium or Cr) same (nickel or Ni)	9627	<u>L15</u>
ALL	corrosion resist\$4 same (chromium or cr)	17843	<u>L14</u>
ALL	111 same 112	3046	<u>L13</u>
ALL	(chromium or Cr) near5 (nickel or Ni)	91641	<u>L12</u>
ALL	(atomiz\$4 or atomis\$4 or atomization or atomisation or spray\$3)	486785	<u>L11</u>
ALL <sub>.</sub>	(atomiz\$4 or atomis\$4 or atomization or atomisation or spray\$3) same (nickel or Ni) near4 (% or percent) same (chromium or Cr)near\$4 (% or percent)	0	<u>L10</u>
ALL	(atomiz\$4 or atomis\$4 or atomization o atomisation) same (nickel or Ni) near4 (% or percent) same (chromium or Cr)near\$4 (% or percent)	0	<u>L9</u>
ALL	(atomiz\$4 or atomis\$4 or atomization o atomisation) same (nickel or Ni) same (chromium or Cr)	609	<u>L8</u>
ALL	corrosion resist\$4 same high (chromium or Cr) content	131	<u>L7</u>
ALL	14 and corrosion resist\$4	332	<u>L6</u>
ALL	11 and corrosion resist\$4	1065	<u>L5</u>
ALL	(chromium or Cr) near3 (40% or 40 percent) same (nickel or Ni)	993	<u>L4</u>
ALL	(chromium or Cr) near4 (40% or 40 percent) same (nickel or Ni)	1189	<u>L3</u>
ALL	(chromium or Cr) same (nickel or Ni) same (40% or 40 percent)	3111	<u>L2</u>
ALL	corrosion resist\$4 same (40% or 40 percent)	1065	<u>L1</u>